

# PHYS 3038 Optics

## L11 Polarization

### Reading Material: Ch8





Shengwang Du



2015, the Year of Light

# E Vector field



Convention of the xyz coordinator system: Look toward the light source

$$\vec{E}(z, t) = \vec{E}_x(z, t) + \vec{E}_v(z, t)$$


$$\vec{E}_x(z, t) = \hat{\mathbf{i}} E_{0x} \cos(kz - \omega t)$$

$$= \hat{\mathbf{i}} E_{0x} \cos(\omega t - kz)$$

$$\vec{E}_v(z, t) = \hat{\mathbf{j}} E_{0y} \cos(kz - \omega t + \varepsilon)$$

$$= \hat{\mathbf{j}} E_{0y} \cos(\omega t - kz - \varepsilon)$$

# Linear Polarization $\varepsilon = 0$




$$\vec{E} = \vec{E}_x + \vec{E}_y = (\hat{i}E_{0x} + \hat{j}E_{0y}) \cos(\omega t - kz) = E_0 (\hat{i} \cos \theta + \hat{j} \sin \theta) \cos(\omega t - kz)$$


# Linear Polarization $\varepsilon = 0$

63


(a)



(b)



(c)



# Right Circular Polarization


$$E_{0x} = E_{0y} = E_0, \varepsilon = -\frac{\pi}{2}$$

---

$$E_x = E_{0x} \cos(kz - \omega t) \quad - kz) \xrightarrow{z=0} iE_0 \cos \omega t$$

$$E_y = E_{0y} \cos(kz - \omega t + \varepsilon) \quad -y, -z, -v, -\omega, -kz + \frac{\pi}{2}) \xrightarrow{z=0} jE_0 \cos\left(\omega t + \frac{\pi}{2}\right) = -jE_0 \sin \omega t$$

$$\vec{E}_x \cdot \vec{E}_x + \vec{E}_y \cdot \vec{E}_y = E_0^2$$



# Left Circular Polarization


$$E_{0x} = E_{0y} = E_0, \varepsilon = \frac{\pi}{2}$$

---

$$\vec{E}_x = \hat{i}E_0 \cos(\omega t - kz) \xrightarrow{z=0} \hat{i}E_0 \cos \omega t$$

$$\vec{E}_y = \hat{j}E_0 \cos(\omega t - kz - \frac{\pi}{2}) \xrightarrow{z=0} \hat{j}E_0 \cos\left(\omega t - \frac{\pi}{2}\right) = \hat{j}E_0 \sin \omega t$$

$$\vec{E}_x \cdot \vec{E}_x + \vec{E}_y \cdot \vec{E}_y = E_0^2$$



# Elliptical Polarization

$$E_{0x} \neq E_{0y} \quad \varepsilon \neq 0$$



$$E_x = E_{0x} \cos(kz - \omega t)$$

$$E_v = E_{0y} \cos(kz - \omega t + \varepsilon)$$

$$E_v/E_{0v} = \cos(kz - \omega t) \cos \varepsilon - \sin(kz - \omega t) \sin \varepsilon$$

and combine it with  $E_x/E_{0x}$  to yield

$$\frac{E_v}{E_{0v}} - \frac{E_x}{E_{0x}} \cos \varepsilon = -\sin(kz - \omega t) \sin \varepsilon \quad (8.13)$$

It follows from Eq. (8.11) that


$$\sin(kz - \omega t) = [1 - (E_x/E_{0x})^2]^{1/2}$$

so Eq. (8.13) leads to

$$\left( \frac{E_v}{E_{0v}} - \frac{E_x}{E_{0x}} \cos \varepsilon \right)^2 = \left[ 1 - \left( \frac{E_x}{E_{0x}} \right)^2 \right] \sin^2 \varepsilon$$


Finally, on rearranging terms, we have

$$\left( \frac{E_v}{E_{0v}} \right)^2 + \left( \frac{E_x}{E_{0x}} \right)^2 - 2 \left( \frac{E_x}{E_{0x}} \right) \left( \frac{E_v}{E_{0v}} \right) \cos \varepsilon = \sin^2 \varepsilon \quad (8.14)$$



This is the equation of an ellipse making an angle  $\alpha$  with the  $(E_x, E_v)$ -coordinate system (Fig. 8.6) such that


$$\tan 2\alpha = \frac{2E_{0x}E_{0y} \cos \varepsilon}{E_{0x}^2 - E_{0y}^2} \quad (8.15)$$



# Natural Light



❖ Unpolarized light: Randomly polarized light




# Spin (Angular Momentum) VS Polarization

---

$$S = 1, m_s = -1, 0, 1$$

$$J_z = -\hbar, 0, \hbar$$




Question: Where is  $J_z = 0$ ?

# Polarizers




- ❖ Linear polarizer
- ❖ Circular polarizer
- ❖ Elliptical polarizer



**Figure 8.10** Natural light incident on a linear polarizer tilted at an angle  $\theta$  with respect to the vertical.

# Linear Polarizer



$$I(\theta) = \frac{c\epsilon_0}{2} E_{01}^2 \cos^2 \theta$$

# Question


---



input

$$E_x = E_{0x} \cos(kz - \omega t)$$

$$E_y = E_{0y} \cos(kz - \omega t + \varepsilon)$$



What is the output?

# Retarders (Wave Plates)



$$\vec{E}_x(z, t) = \hat{\mathbf{i}} E_{0x} \cos(kz - \omega t) = \hat{i} E_{0x} \cos(\omega t - kz) \Rightarrow \hat{i} E_{0x} \cos(\omega t)$$

$$\vec{E}_y(z, t) = \hat{\mathbf{j}} E_{0y} \cos(kz - \omega t + \varepsilon) = \hat{j} E_{0y} \cos(\omega t - kz - \varepsilon) \Rightarrow \hat{j} E_{0y} \cos(\omega t - \varepsilon)$$





$$\vec{E}_x = \hat{i} E_{0x} \cos(\omega t - k_x z) \Rightarrow \hat{i} E_{0x} \cos(\omega t)$$

$$\vec{E}_y = \hat{j} E_{0y} \cos(\omega t - k_y z - \varepsilon) \Rightarrow \hat{j} E_{0y} \cos[\omega t - (k_y - k_x)z - \varepsilon]$$

$$\Delta\varphi = (k_y - k_x)z + \varepsilon$$

# Retarders (Wave Plates)



$$k_s = n_s k_0 > k_f = n_f k_0$$

$$\Delta\varphi_{fs} = (k_s - k_f)d = \frac{2\pi}{\lambda_0} d(n_s - n_f)$$

$$\Delta\varphi_{fs} = \frac{1}{\#} \times 2\pi$$

1/# Wave plate

# Half-Wave Plate

$$\Delta\varphi_{fs} = \frac{1}{2} \times 2\pi + 2m\pi = \pi + 2m\pi$$




m=0, zero-order

m≠0, multiple-order

Input

$$\vec{E}_x = \hat{i}E_0 \cos \theta \cos(\omega t)$$

$$\vec{E}_y = \hat{j}E_0 \sin \theta \cos(\omega t)$$



Output

$$\vec{E}_x = \hat{i}E_0 \cos \theta \cos(\omega t)$$

$$= \hat{i}E_0 \cos(-\theta) \cos(\omega t)$$


$$\vec{E}_y = \hat{j}E_0 \sin \theta \cos(\omega t - \pi)$$

$$= -\hat{j}E_0 \sin \theta \cos(\omega t)$$

$$= \hat{j}E_0 \sin(-\theta) \cos(\omega t)$$

“Reflection” according to the fast axis

# Half-Wave Plate



# Quarter-Wave Plate


$$\Delta\varphi_{fs} = \frac{1}{4} \times 2\pi + 2m\pi = \frac{\pi}{2} + 2m\pi \quad m\text{-order}$$



m=0, zero-order

m≠0, multiple-order

Y, slow axis



Input  $\vec{E}_x = \hat{i} \frac{1}{\sqrt{2}} E_0 \cos(\omega t)$  Linearly polarized

$$\vec{E}_y = \hat{j} \frac{1}{\sqrt{2}} E_0 \sin \theta \cos(\omega t)$$


Output

$$\vec{E}_x = \hat{i} \frac{1}{\sqrt{2}} E_0 \cos(\omega t)$$
$$\vec{E}_y = \hat{j} \frac{1}{\sqrt{2}} E_0 \cos(\omega t - \pi/2)$$
$$= \hat{j} \frac{1}{\sqrt{2}} E_0 \sin(\omega t)$$

Left circularly polarized

Linear polarization → Circular polarization

# Quarter-Wave Plate




**Figure 8.40** A quarter-wave plate transforms light initially linearly polarized at an angle  $45^\circ$  (oscillating in the first and third quadrants) into left circular light (rotating counterclockwise looking toward the source).

# Quarter-Wave Plate



$$\Delta\varphi_{fs} = \frac{1}{4} \times 2\pi = \frac{\pi}{2}$$

Y, fast axis



Input

$$\vec{E}_x = \hat{i} \frac{1}{\sqrt{2}} E_0 \cos(\omega t)$$

$$\vec{E}_y = \hat{j} \frac{1}{\sqrt{2}} E_0 \sin \theta \cos(\omega t)$$

Linearly polarized

Output

$$\vec{E}_x = \hat{i} \frac{1}{\sqrt{2}} E_0 \cos(\omega t - \pi/2)$$

$$= \hat{i} \frac{1}{\sqrt{2}} E_0 \sin(\omega t)$$

$$\vec{E}_x = \hat{j} \frac{1}{\sqrt{2}} E_0 \cos(\omega t)$$

Right circularly polarized

Linear polarization → Circular polarization

# Manipulating Polarization

---



- ❖ Combining a half-wave plate and quarter-wave plate, one can change a polarization to an arbitrary polarization.
- ❖ Combining a half-wave plate, quarter-wave plate, and a linear polarizer, one can construct an arbitrary polarizer.